

6500u 3G Data Card Modem



The E-Lins 6500u 3G Data Card Modem is a complete 3.5G/3.75G enabled wireless USB data modem designed to offer high-speed wireless connectivity for Windows notebook and desktop computers on HSDPA/HSUPA networks. It is easy to use USB connector and the ability to roam globally on tri-band UMTS and quad-band GSM/ EDGE networks. It enables connection to internet download speed up to 7.2Mbps.

The compact USB modem no need to install drivers from a CD because the software is included on the device. It also built-in a MicroSD memory (T-Flash memory) expansion no matter whether connects with the Internet or not. The only 88(L) x 26(W) x 10(H) mm mm dimension is small enough to fit comfortably in any pocket.

- Worldwide use with tri-band UMTS and quad-band GSM/ EDGE operation.
- Capable of wireless data speed up to 7.2Mbps download and 384kbps upload.
- Receive SMS messages,
- Voice optional
- Accessing E-mail and browsing the WEB.
- USIM card functionality.
- MicroSD memory expansion.
- Zero install software, No CD required for windows.
- Support Windows xp, vista, win7 32/64 bits; Support Android, Linux optional

Technical Specifications

>>Technology/Bands:

UMTS/HSDPA/HSUPA 2100 MHz 3GPP R5, or 2100/850Mhz, or 2100/1900Mhz or 900/850Mhz or 850/1900Mhz optional

Quad-band GSM/ EDGE 850/900/1800/1900MHz 3GPP R99

6500d HSDPA Version:

Data transmission up to 7.2Mbps (HSDPA)

E-Lins Technology Co., Limited

Add: Bld.22, Longxi Garden, Nonglin Rd., Futian District, Shenzhen, 518000, China

Tel: +86-0755-81220758 Fax: +86-755-83700465 E-mail: sales@e-lins.com www.e-lins.com

Data transmission up to 384Kbps (UMTS)

Data transmission up to 384Kbps (EDGE)

6500u HSUPA Version:

Data transmission up to 7.2Mbps/14.4Mbps download (HSUPA), 5.76Mbps upload

Data transmission up to 384Kbps (UMTS)

Data transmission up to 384Kbps (EDGE)

Memory: 2Gbit NAND+32Mbit SDRAM

Network Roam/reselect: manual and automatic choice GPRS/UMTS

>>Dimensions and Weight:

88(L) x 26(W) x 10(H) mm

22g

>>Visual Indicator:

Double color LED indicator express Multi-meaning for real-time service status, technology modes, and error conditions

>>External Interface:

USB 2.0 interface with PC

Internal Antenna Built-in 5 bands

SIM card slot

1 Double Color LED Indicator

>>Environmental:

Operating Temperature: -20 to +60° C

Storage Temperature: -30 to +85° C

>>Operating Systems Support:

Windows2000, Windows XP, Windows Vista , Windows 7, Ubuntu 8.04, Mac os x 10.4; Android, LUNIX

>> System Requirements:

Card Slots: USB Interface

Memory: 32 MB

Disk Space: 32 MB

System: Pentium 150MHz or higher

>> Standard Package Contents:

6500 Modem

USB cable

E-Lins Technology Co., Limited

Add: Bld.22, Longxi Garden, Nonglin Rd., Futian District, Shenzhen, 518000, China

Tel: +86-0755-81220758 Fax: +86-755-83700465 E-mail: sales@e-lins.com www.e-lins.com

Quick Start Guide
Retail packaging